

INSTALLERS

RM 2430
SLH 2430

LARGE ROLL TURF INSTALLERS

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation



YOU'LL SEE MORE BUSINESS AND A LOT FEWER SEAMS.

The RM 2430 and SLH 2430 from Brouwer are the products to have on hand for every large roll installation project. The RM 2430 is deceptively powerful for its size, able to lift a roll of turf weighing up to 1500 lbs. and lay 24" or 30" wide large rolls. Its low center of gravity makes it perfect for turf installation on banks and slopes up to 20 degrees. The SLH 2430 is the ideal choice in tractor-mounted large roll installers. With the help of bearings, the SLH 2430 unrolls turf without tearing and lays it quickly, but gently and precisely. Easy to own, operate and maintain, the RM 2430 and SLH 2430 are the peak in turf installation performance.



SLH 2430 3-Point Hitch Features:

- 3-point hitch design (fits standard 3-point hitch)
- Using tractor hydraulics, the operator can clamp and raise the roll for transport from the seat
- Turf turns on bearings for easy unrolling without tearing the turf
- Turf can be handled and unrolled without the use of core tubes
- Heavy steel frame
- Inexpensive to own and maintain
- Easily adaptable to install either 24" or 30" wide rolls of turf

SLH 2430 3-Point Hitch Specifications

Roll Capacity	Width 24" and 30"
	Diameter 48"
Clamp	Hydraulic
Categories	One & two, 3-Point
Tubes	Use with or without

RM 2430 Walk Behind Features:

- Excellent for large roll installation on slopes
- Durable heavy steel frame
- Hydrostatic transmission
- Pivoting rear tire steering means minimal turf damage or scuffing, excellent maneuverability
- Extremely easy to operate
- 1.5 gal. fuel tank



RM 2430 Walk Behind Specifications

Width	70" (1778 mm)
Length	84" (2134 mm)
Height	39" (991 mm)
Weight	975 lbs. (442 kg)
Wheelbase	58" (Center to center of tires)
Tires	Front: 24x12-12 turf tread Rear: 18x9.50-8 straight rib
Fuel Capacity	1.5 gal. (5.68 liters)
Controls	F-N-R Control and Cable to lift
Lift	2 cylinders, 2" bore x 8" stroke
Steering	Height adjustable handle to pivoting rear tire
Drive	Infinitely variable hydrostatic drive to hydraulic motors in front wheels
Ground Clearance	7" (17.78 cm)
Engine	8.5 hp Honda, horizontal shaft, electric start, Industrial/commercial
Roll Capacity	Width 24" and 30" Weight 2000lbs (907.2 kg)
Speed	0 - 4.7 mph (0 - 7.56 kph) Infinitely variable forward/reverse



TEL: 905-476-6222 • 1-888-341-5113
 FAX: 905-476-6744
 US Parts TEL: 1-800-314-1008
 23324 Woodbine Avenue, Keswick, Ontario L4P 3E9
 email: info@kesmac.com • www.brouwerturf.com

Specifications subject to change without notice or obligation.
 Printed in Canada 01/11