
#### THERE ARE 3 MODELS OF VACUUM TO CHOOSE FROM IN THE

## **MULTI-VAC SERIES**

MODEL 772: 7 CUBIC YARD HOPPER / 72" PICK-UP HEAD. MODEL 1096: 10 CUBIC YARD HOPPER / 96" PICK-UP HEAD. MODEL 10120: 10 CUBIC YARD HOPPER / 120" PICK-UP HEAD.







A PLATFORM LOCATED AROUND THE BLOWER HOUSING ENABLE THE OPERATOR TO SAFELY & PROPERLY CLEAN OUT THE INSIDE OF THE BLOWER. A DRAIN TRAP IS LOCATED AT THE BOTTOM OF THE BLOWER TO DRAIN WATER AND RESIDUES. ONCE THE HOPPER IS TILTED, IT IS QUICK AND EASY TO WASH OUT THE INSIDE.



# **MULTI-VAC SERIES**

SPECIFICATIONS			
	MULTI- VAC 772	MULTI- VAC 1096	MULTI- VAC 10120
PICK-UP HEAD WIDTH	72 INCHES ( 180 CM )	96 INCHES ( 240 CM )	120 INCHES ( 300 CM )
HYDRAULIC LIFT PICK-UP HEAD	STANDARD	STANDARD	STANDARD
PICK-UP HEAD DOUBLE ADJUSTABLE ROLLER	STANDARD	STANDARD	STANDARD
REAR FLOATATING ROLLER	STANDARD	STANDARD	STANDARD
FLAIL NYLON HAMMER BRUSH	AVAILABLE 72 INCHES WIDE	AVAILABLE 96 INCHES WIDE	AVAILABLE 120 INCHES WIDE
VERTI-TATCH BRUSH	AVAILABLE 72 INCHES WIDE	AVAILABLE 96 INCHES WIDE	AVAILABLE 96 INCHES WIDE
OPTIONAL SLICER KIT	72 INCHES WIDE	96 INCHES WIDE	96 INCHES WIDE
MECHANICAL BRUSH DRIVE	STANDARD	STANDARD	STANDARD
IMPELLER SIZE	32 3/4" X 12 3/8" ( 82 X 31 CM )	38 3/4" X 12 3/8" ( 96 X 31 CM )	38 3/4" X 12 3/8" ( 96 X 31 CM )
NO. OF IMPELLER BLADES	4 (1/4" THICK- 6.35 MM )	4 (1/4" THICK- 6.35 MM )	4 (1/4" THICK- 6.35 MM )
IMPELLER RATATION SPEED	1190 RPM	1050 RPM	1050 RPM
BOTTOM DRAIN TRAP ON BLOWER HOUSING	STANDARD	STANDARD	STANDARD
ROTARY SHREDDER	STANDARD	STANDARD	STANDARD
ANTI-BLOCAGE ROTARY BLADE FOR BRANCHES	STANDARD	STANDARD	STANDARD
MAINTENANCE-FREE OIL BATH DRIVE SYSTEM	STANDARD	STANDARD	STANDARD
HYDRAULIC TILT DUMP	STANDARD	STANDARD	STANDARD
4 WHEELS ON WALKING BEAM AXLES	STANDARD	STANDARD	STANDARD
TIRE DIMENSION	24 X 13 - 12 TURF SAVER	24 X 13 - 12 TURF SAVER	24 X 13 - 12 TURF SAVER
RECOMMENDED TRACTOR HP AT PTO	40 HP	50 HP	50 HP
HITCH TYPE	ADJUSTABLE DRAW BAR	ADJUSTABLE DRAW BAR	ADJUSTABLE DRAW BAR
LOW DISCHARGE AIR EXHAUST	STANDARD	STANDARD	STANDARD
HOPPER CAPACITY	7 CU. YARD OF SHREDDED DEBRIS	10 CU. YARD OF SHREDDED DEBRIS	10 CU. YARD OF SHREDDED DEBRIS
OPTIONAL HAND PICKUP HOSE	10" X 16 FT ( 25.5 CM X 4.8 M)	12" X 16 FT ( 30 CM X 4.8 M)	12" X 16 FT ( 30 CM X 4.8 M)
TURN AND STOP ROAD LIGHT KIT	OPTIONAL	OPTIONAL	OPTIONAL
NOISE LEVEL	89 DECIBEL	89 DECIBEL	89 DECIBEL
MACHINE OVERALL LENGTH	214" (535 CM)	226" (565 CM)	226" (565 CM)
MACHINE OVERALL WIDTH	78" (195 CM)	102" (255 CM)	126" (315 CM)
MACHINE HEIGHT	91" (227.5 CM)	101" (252.5 CM)	101" (252.5 CM)
MACHINE WEIGHT	4990 LBS (2263 KG)	5700 LBS (2586 KG)	5800 LBS (2630 KG)
SHIPPING DIMENSION	186" X 79" X 91"HIGH (463 X 197.5 X 227.5 CM)	199" X 84.5" X 101"HIGH (506 X 211 X 252.5 CM)	199" X 84.5" X 101"HIGH (506 X 211 X 252.5 CM)

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment & accessories, and may not illustrate all standard equipment.

#### **LEADER IN LEAF AND DEBRIS HANDLING EQUIPMENT**



Part number: NC13-72-0061

Wickham, Québec Canada, JOC 150

**T : 1 819 398-6883** SF : 1 888 398-6883 F : 1 800-529-5311 service@agrimetal.com

# **MULTI-VAC SERIES**

**LEAF AND DEBRIS VACUUMS** 



# DESIGNED FOR THE MOST DEMANDING SUPERINTENDENT

LEADER IN LEAF AND DEBRIS HANDLING EQUIPMENT





#### REDUCED IMPELLER RPM

The large format design of the vacuum housing allows us to reduce the impeller RPM.

#### THE BENEFITS ARE :

- Quiet operating level for the operator and surrounding neighbours.
- Eliminate noise pollution.



A greater holding hopper capacity with AgriMetal Multi-Vac series. The Multi-Vac series has 12 fixed knives installed just before the impeller housing, two rotary blades turning at high speed to shred leaves & branches and a third rotary blade located inside the pick-up head throat to eliminate any clogging. This exclusive internal shredder greatly increases the volume of debris that is packed into the hopper.

#### THE BENEFITS OF THIS EXCLUSIVE DESIGN ARE:

- To prevent the operator from having to stop and unclog the pick-up
- It allows a much longer time between trips to the dump site
- Increases productivity.



The pick-up head lowers and rises hydraulically from the operator's seat. As the operator lifts the pick-up head, the front raises first which allows to vacuum thick piles of leaves. The pickup head rides on 4 large rollers to eliminate marking, compacting and scuffing fairways.



AgriMetal has developed a new brush system that is second to none in sweeping leaves and branches. The brush is made of 3/8" wide high-strength nylon fingers with shorter steel knives located between the nylon fingers. The nylon fingers and steel knives are made to freely pivot so as not to damage the turf, while throwing leaves and branches into the intake.



The standard vacuum head of the Multi-Vac may be replaced with a Verti-Tatch head to dethatch & pick-up debris all in one pass. (spacing 1 ½ inch cc.)



THE FRONT ROLLER HEIGHT ADJUSTMENT IS EASILY DONE WITHOUT THE NEED OF TOOLS.



An optional slicer kit can be attached to the Verti-Tatch head. Slicer blade follow the same path as the Veticut blades for deeper penetration. (1 inch x 1 ¾ inch deep) The Verti-Tatch head equipped with a Slicer kit allow you to: de-tatch, collect & aerate fairways all in one pass. This multi purpose pick up head becomes a cost efficient investment because of its year-round use and multiple application. Only 15 minutes is required to switch pick up heads.



### LOW GROUND PRESSURE

2 SETS OF WHEELS, MOUNTED ON WALK-ING BEAM AXLES TO ENSURE LOW GROUND PRESSURE AND ELIMINATE SCUFFING IN TIGHT TURNS.



### **SUCTION HOSE**

AN OPTIONAL 16 FOOT COMMERCIAL SUCTION HOSE IS AVAILABLE ON ALL MODELS.



### **EXHAUST**

THE EXHAUST OF THE MULTI-VAC SERIES EXPEL
THE VICIOUS AIR AT THE BOTTOM OF THE REAR
DOOR, DIRECTING THE DUST STRAIGHT TO THE

