

INSTALLERS

RM 2442 & 2448

LARGE ROLL TURF INSTALLER

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation



YOU'LL SEE MORE BUSINESS AND A LOT FEWER SEAMS.

The ROLLMATE RM 2442 & 2448 Sod Layer is the ideal sod layer for sod growers, landscapers, rental outlets, and other contractors. The 42" or 48" wide, 4 foot 48" diameter, 2000 pound roll capacity along with the exceptional maneuverability, make the RM 2442 & 2448 an ideal choice for most sod laying applications. A reliable Honda 11.0 HP Industrial/Commercial engine drives through a field-proven infinitely variable hydrostatic drive to hydraulic motors in front wheels that shifts effortlessly from forward to reverse with a single lever control mounted on the steering handle. The sod roll can be lifted by inserting the adjustable mandrel in the sod roll and mounting it onto the lift arms. The Brouwer ROLLMATE SOD LAYER is an outstanding machine for operating on slopes, highly maneuverable and easy to operate.

RM 2442 & 2448 Walk Behind Features:

- Excellent for large roll installation on slopes
- Durable heavy steel frame
- Hydrostatic transmission
- Pivoting rear tire steering means minimal turf damage or scuffing, excellent maneuverability
- Easy to operate
- 1.5 gal. fuel tank



TEL: 905-476-6222 • 1-888-341-5113

FAX: 905-476-6744

US Parts TEL: 1-800-314-1008

23324 Woodbine Avenue, Keswick, Ontario L4P 3E9

email: info@kesmac.com • www.brouwerturf.com

RM 2442 Walk Behind Specifications

Width	83" (211 cm)
Height	39" (99 cm)
Weight	1090 lbs. (494 kg)
Wheelbase	59.5" (Center to center of tires)
Tires	Front: 24x12-12 turf tread Rear: 18x9.50-8 straight rib
Fuel Capacity	1.5 gal. (5.68 liters)
Controls	Spring centered control levers and cables to hydrostatic pump and lift valve
Lift	2 cylinders, 2" bore x 8" stroke
Steering	Height adjustable handle to pivoting rear tire
Drive	Infinitely variable hydrostatic drive to hydraulic motors in front wheels
Ground Clearance ..	7" (17.8 cm)
Engine	11 hp Honda, horizontal shaft, electric start, Industrial/commercial
Roll Capacity	Width 42" (106.7 cm) Weight 2000 lbs (907.2 kg)
Speed	0 - 4.7 mph (7.56 kph) Infinitely variable forward/reverse

RM 2448 Walk Behind Specifications

Width	89" (226 cm)
Height	39" (99 cm)
Weight	1150 lbs. (521 kg)
Tires	Front: 24x12-12 turf tread Rear: 18x9.50-8 straight rib
Fuel Capacity	1.5 gal. (5.68 liters)
Controls	Spring centered control levers and cables to hydrostatic pump and lift valve
Lift	2 cylinders, 2" bore x 8" stroke
Steering	Height adjustable handle to pivoting rear tire
Drive	Infinitely variable hydrostatic drive to hydraulic motors in front wheels
Ground Clearance ..	7" (17.8 cm)
Engine	11 hp Honda, horizontal shaft, electric start, Industrial/commercial
Roll Capacity	Width 48" (122 cm) Weight 2000 lbs (907.2 kg)
Speed	0 - 4.7 mph (7.56 mph) Infinitely variable forward/reverse